



BATH + LIGHT

ALINA 7W


LED ALINA COB DOWNLIGHT

Indoor Luminaire

Product Code:

LALN01R007XC / LALN01R007XN / LALN01R007XW

7W - 540lm - 6500K - CRI>90 Ra - Beam Angle: 40°



Technical Specifications


Operating Temperature	-10°C to 40°C
Rated Input Voltage & Frequency	230 VAC, 50Hz
Rated Input Wattage	7W \pm 10%
Rated Input Current	0.032 Amp (Nominal)
Power Factor	\geq 0.90
ATHD	<20%
Rated Luminous Flux	540 lm / 525 lm / 490 lm (tolerance as per BIS)
Rated Luminaire Efficacy	80 lm/W / 75 lm/W / 70 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	6500 K / 4000 K / 3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>90 Ra
Beam Angle	40°
Driver Efficiency	\geq 80%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	PC. Housing
Lens / Reflector	PC. Diffuser
Mounting	Recess

Protections

Over Voltage Protection	Withstand upto 440V/AC for 4 Hrs.
Surge Protection	\pm 4.0KV
Protection Class	Class II
Ingress Protection (IP Rating)	IP20
Impact Protection (IK Rating)	IK02
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

Light Distribution




UGR Table

ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise						Viewed endwise				
x = 2H y = 2H		18.1	19.0	18.3	19.1	19.3	17.8	18.6	18.0	18.8	19.0
	3H	18.0	18.7	18.2	18.9	19.1	17.6	18.4	17.9	18.6	18.8
	4H	17.9	18.6	18.2	18.8	19.0	17.6	18.3	17.8	18.5	18.7
	6H	17.8	18.5	18.1	18.7	19.0	17.5	18.2	17.8	18.4	18.6
	8H	17.8	18.4	18.1	18.7	18.9	17.4	18.1	17.7	18.3	18.6
	12H	17.7	18.3	18.0	18.6	18.9	17.4	18.0	17.7	18.3	18.5
4H	2H	17.9	18.6	18.2	18.8	19.1	17.6	18.3	17.8	18.5	18.7
	3H	17.7	18.4	18.0	18.6	18.9	17.4	18.0	17.7	18.3	18.6
	4H	17.6	18.2	18.0	18.5	18.8	17.3	17.9	17.6	18.2	18.5
	6H	17.5	18.0	17.9	18.4	18.7	17.2	17.7	17.6	18.0	18.4
	8H	17.5	17.9	17.9	18.3	18.7	17.1	17.6	17.5	18.0	18.3
	12H	17.4	17.9	17.8	18.2	18.6	17.1	17.5	17.5	17.9	18.3
8H	4H	17.5	17.9	17.9	18.3	18.7	17.1	17.6	17.5	18.0	18.3
	6H	17.4	17.8	17.8	18.1	18.6	17.0	17.4	17.5	17.8	18.2
	8H	17.3	17.7	17.8	18.1	18.5	17.0	17.3	17.4	17.7	18.2
	12H	17.3	17.5	17.7	18.0	18.5	16.9	17.2	17.4	17.7	18.1
12H	4H	17.4	17.9	17.8	18.2	18.6	17.1	17.5	17.5	17.9	18.3
	6H	17.3	17.7	17.8	18.1	18.5	17.0	17.3	17.4	17.7	18.2
	8H	17.3	17.6	17.7	18.0	18.5	16.9	17.2	17.4	17.7	18.1
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 4.3 / -12.6						+ 4.0 / -11.9				
1.5H	+ 6.8 / - 8.5						+ 6.4 / - 7.8				
2.0H	+ 4.2 / - 6.8						+ 4.1 / - 6.0				

With our continuous efforts to upgrade the technology/product, all product specifications and data are subject to change without prior notice. We always try to maintain the accuracy of our product images, but due to different viewing conditions, the colors may vary. Images are only for indicative purpose.

Product Dimensions (Dia. x H)

Ø89x70 mm, Cutout Ø75 mm



Applications

Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.