

- CALLIA CHINATON	
Product Code	KUS-WHM-35953BIUFPM
Brand	Jaquar
In Colours	White Matt, Grey Matt, Beige Matt, Black Matt
Туре	Wall Hung WC
Material	Ceramic-Vitreous China (VC)
PRODUCT SPECIFICATION	
Product Dimension	380x525x375mm
Bowl Inner Dimension	270x330 mm
Product Net Weight	30 kg.
Product Gross Weight	35 kg
Packaging Dimension	450 X 390 X 535 mm
Outlet	Horizontal
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole Ø 55 +3/-1 mm
	External diameter of outlet hole dia. $\emptyset$ 100 $\pm$ 5 mm
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 210 mm

## PRODUCT FEATURES


LPF

Rimless Blind Installation Wall Hung WC	(L) From wall tile surface to center of seat cover fixing hole
With UF Soft Close Seat Cover, Hinges	(La) WC Fixing wall thickness

And Accessories Set, Dual Flush-3/6 (Lb) From wall tile surface to the inner bowl

surface of WC

Anti Germ Glaze, Trap glazed.



ACCESSORIES INCLUDED	CESSORIES INCLUDED	
Seat Cover	KUS-WHM-35101UFPM	
Inlet & Outlet gasket	ZPS-WHT-GK01	
Fixing kit	ZPS-WHT-FB13	

## ACCESSORIES RECOMMENDATION

Rag bolt	ZPS-MST-RB07N
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431FS

## CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- Risk of external leakage. Do not lift or rock the bowl after placement
- $_{ extsf{q}}$  Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- n Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- Recommended to use Genuine Accessories.

## QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance  $\pm\,5$  MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. For Installation Refer Actual Product.Last modified on 25 August 2025.