



<b>Product Code</b>	ALD-CHR-055N
<b>Description</b>	Concealed Body for Single Lever Diverter 35mm Cartridge with Button Assembly, (Button On Top) But without Exposed Part
<b>Flow Rate</b>	27.77 LPM @ 3 bar
<b>Recommended Water Pressure</b>	0.5 Bar - 5 Bar
<b>Brass Specification in Percentage</b>	<p><b>Brass Ingots as per IS:1264-1997</b> Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p>
<b>Cartridge Specification</b>	<p>Cartridge with Temperature Limiter</p> <p>Cartridge with Brass Spindle</p> <p>Life Cycle EN 817: 70,000 cycles (Standard)</p> <p>- 2.1 LAC Cycles as per EN 817*</p> <p>- 10.5 LAC Cycles (ON/OFF)*</p>
<b>Water Tightness</b>	16 bar (Pass)
<b>Pressure Resistance</b>	25 bar (Pass)
<b>Available Colour Finishing</b>	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	