



Product Code	FLP-CHR-5009BPM
Description	Single Lever Sink Mixer with 210mm Extension Body Swinging Spout without Popup Waste (Table Mounted) with 600mm Long Braided Hoses
Connection Size	Braided hoses, 1/2" FIP (WRAS Approved) Withstand pressure of 10 Bar
Flow Rate	13.24 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in Percentage	<p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p>Brass Pipe as per IS:407-1996 Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p>
Cartridge Specification	<p>Cartridge with Temperature Limiter</p> <p>Cartridge with Brass Spindle</p> <p>Life Cycle EN 817: 70,000 cycles (Standard)</p> <p>- 2.1 LAC Cycles as per EN 817*</p> <p>- 10.5 LAC Cycles (ON/OFF)*</p>
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	<p>Plating: Nickel-10.0 micron Chromium-0.3 micron</p> <p>Salt Spray (500 hrs + Validated)</p> <p>Adhesion (Pass)</p>
Aerator Size	WRAS, ACS Approved (20X1)
Available Colour Finishing	Black Chrome (BCH) & Black Matt (BLM)
* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	