





JCS-WHT-2400WS	
Single Piece Slim Concealed Cistern With Wall Mounting Frame, Installation Kit And "S-Type Drain Pipe Connection Set For Wall Hung Wc (Without Flush Control Plate)	
	3.0/6.0 LPF
• Tank body: Strong 80 mm thick High-density polyethylene (HDPE) 'Single-piece' body.	
• Anti-Condensation Lining: Anti condensation lining of 6mm thick wall takes care of	
temperature change.	
• Inlet & Outlet Valves: Inlet valve has a special rotary structure which gives out low noise &	
anti siphon function. Both valves (Inlet & outlet) are WARS approved.	
• Working Pressure: 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive	
water supply)	
• Life Cycles of Mechanism: The lifetime of sea water test and dirty water test have passed	
<ul> <li>100,000 cycles</li> <li>Flush Control Plates: ABS made chrome plated flush control plates which is compatible for Single Piece Slim in-wall Cistern (JCS-WHT-2400WS)</li> <li>Wall Mounted Frame: oxford blue Powder coated steel frame.</li> </ul>	
	• Water inlet: ½" water supply connection from top.
	• Flush volume: Factory setting 6.0~3.0 litres, Eco adjustable: 4.0~2.0 litres (Only for WC
	pans designed for low volume flushing).
For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres	
<ul> <li>Solid pre-wall installation system for brick &amp; solid walls</li> <li>For installation in a load bearing stud wall.</li> <li>Not suitable for installation in a drywall</li> </ul>	

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.