




Product Code	JCS-WHT-2400S
Description	Single Piece Slim Concealed Cistern Body with Installation Kit & "S-Type" drain pipe connection set for Wall Hung WC (without Flush Control Plate)
Flow Rate	3.0/6.0 LPF
Features	• Tank body: Strong 80 mm thick High-density polyethylene (HDPE) 'Single-piece' body. • Anti-Condensation Lining: Anti condensation lining of 6mm thick wall takes care of temperature change. • Inlet & Outlet Valves: Inlet valve has a special rotary structure which gives out low noise & anti siphon function. Both valves (Inlet & outlet) are WARS approved. • Working Pressure: 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water supply) • Life Cycles of Mechanism: The lifetime of sea water test and dirty water test have passed 100,000 cycles • Flush Control Plates: ABS made chrome plated flush control plates which is compatible for Single Piece Slim in-wall Cistern (JCS-WHT-2400S) • Water inlet: ½" water supply connection from top. • Flush volume: Factory setting 6.0~3.0 litres, Eco adjustable: 4.0~2.0 litres (Only for WC pans designed for low volume flushing).
Application	• For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres • For installation in a load bearing stud wall.
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	