





Product Code	LAG-CHR-91189PSL
Description	3-Hole Basin Mixer with Pipe Spout, Lever Handle and without Popup Waste System
Flow Rate	16.83 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0
	LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 4.0 Bar pressure) one can regulate the
	flow rate.
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in Percentage	Brass Ingots as per IS:1264-1997
	Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total
	Impurity (0.0-2.0), Zn (Remainder)
	Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
	Brass Pipe as per IS:407-1996
	Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)
	Fittings: Components have WRAS Approved for food grade conformity with Brass
Cartridge Specification	Housing and Spindle
	1 - '
	Life Cycle EN 200: 200,000 cycles (Standard)
	- 5.0 LAC Cycles as per EN 200*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron
	Salt Spray (500 hrs + Validated)
	Adhesion (Pass)
Aerator Size	WRAS, ACS Approved (20X1)
Available Single Colour	Black Chrome (BCH), Black Matt (BLM), Gold Matt-PVD (GMP), Gold Bright-PVD (GBP) &
Finishing	Blush Gold Bright PVD (BGP)
Available Dual Colour Finishing	  Black Matt & Black Chrome (BBC), Gold Matt-PVD & Gold Bright-PVD (GMG), Black Matt &
(First Colour for Body & Second	Gold Matt-PVD (BGM)
for Lever)	

<sup>\*</sup> As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.