



| | |
|---|---|
| Product Code | OHS-CHR-1691 |
| Description | Duoflo Shower Square Shape 250 X 250mm AISI 304 stainless steel with Installation kit for false ceiling <ul style="list-style-type: none"> • 2-functions <ul style="list-style-type: none"> ▪ Rain, ▪ Laminar |
| Flow Rate | Rain - 67.21 LPM @ 3 bar Laminar - 65.26 LPM @ 3 bar |
| Flow regulator | By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 1.0 Bar - 3.0 Bar |
| Mount Type | Ceiling Mounting |
| Spray Modes | Rain & Laminar Functions |
| Material Composition Specification in Percentage | <p>STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)</p> <p>ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102</p> |
| Technology | Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel. |
| Finish | Salt Spray (350 hrs + Validated) Adhesion (Pass) |
| Available Finishing | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) & Stainless Steel (SSF) |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |