



<b>Product Code</b>	OHS-CHR-1693
<b>Description</b>	Duoflo Shower Round Shape 350mm AISI 304 stainless steel with Installation kit for false ceiling <ul style="list-style-type: none"> <li>• 2-functions <ul style="list-style-type: none"> <li>▪ Rain, ▪ 4 X Mist</li> </ul> </li> </ul>
<b>Flow Rate</b>	Rain - 71.34 LPM @ 3 bar Mist - 2.43 LPM @ 3 bar
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Mount Type</b>	Ceiling Mounting
<b>Spray Modes</b>	Rain & Mist Functions
<b>Material Composition Specification in Percentage</b>	<b>STAINLESS STEEL:</b> Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)  <b>ABS:</b> Specific Gravity (g/cm <sup>2</sup> ) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102
<b>Technology</b>	<b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
<b>Finish</b>	Salt Spray (350 hrs + Validated) Adhesion (Pass)
<b>Available Finishing</b>	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP) & Graphite (GRF)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	