





Product Code	OPP-CHR-15653PM
Description	Multifunction Thermostatic Shower Mixer with Integrated Divertor and Provision for Connection to Exposed Shower Pipe (SHA-1211NH or SHA-1213), Overhead & Hand Shower with Connecting Legs & Wall Flange
Flow Rate	35.64 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989
Percentage	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
Specification	 Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure High technology thermoplastic polymer minimises lime-scale build up Standard temperature range: 15° C to 60° C (59-104°F) Shower mixer contains ceramic cartridge for ON & OFF function. Protected against backflow
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Available Colour Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite (GRF) & Stainless Steel Finish (SSF).
* As par in house testing done on automatic life evelo testing machine made by Ciuscani Italy	

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.