



Fixing hole

JAQUAL BATH+LIGHT





	DACK VIEW			
GENERAL INFORMATION				
Product Code	CNS-WHT-853S220SPPSMY			
Brand	Jaquar			
Colour	White			
Туре	Single piece-WC (S trap 220)			
Material	Ceramic-Vitreous China (VC)			
PRODUCT SPECIFICATION				
Product Dimension	360x670x740 mm			
Bowl Opening (Inner Dimension)	260x330 mm			
Product Net Weight	46.5 Kg			

Bowl Opening (Inner Dimension)	260x330 mm	
Product Net Weight	46.5 Kg	
Product Gross Weight	51.5 kg	
Packaging Dimension	700X400X800 mm	
Outlet	Vertical	
Inlet And Outlet Hole Dimension	External diameter of outlet hole dia. Ø 100 ± 5 mm	
iniet And Oddet Hole Diffielision	Horizontal distance between the wall line and the centre line of the waste outlet hole ≤ 220 mm	

TIIDEC	

Product Features	Rimless Single Piece WC With PP Soft Close Slim Seat Covers, with Dual Flush-3/6
	LPF,Anti germ glaze,and flushing kit.
ACCESSORIES INCLUDED	
Seat Cover	SLS-WHT-6103SM
Floor fixing screw	ZPS-SNS-FB10
Wax Seal	ZPS-WHT-1401
DUAL FLUSH FITTINGS	ZCF-WHT-FT002

CARE AND CLEANING GUIDELINES

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- \neg Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- ── Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- ¬ Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product.Last modified on 18 March 2025.