




Product Code	JCS-WHT-2431
Description	Single Piece Concealed Cistern Body (Front or Top Actuation) with Installation Kit (without flush control plate)
Flow Rate	3.0/6.0 LPF
Features	• Tank body: Strong 125mm thick High-density polyethylene (HDPE) 'Single-piece' body. • Anti-Condensation Lining: Anti condensation lining of 6mm thick wall takes care of temperature change. • Inlet & Outlet Valves: Inlet valve has a special rotary structure which gives out low noise & anti siphon function. Both valves (Inlet & outlet) are WARS approved. • Working Pressure: 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water supply) • Life Cycles of Mechanism: The lifetime of sea water test and dirty water test have passed 100,000 cycles • Flush Control Plates: ABS made chrome plated flush control plates which is compatible for Single Piece Concealed Cistern Body (Front or Top Actuation) JCS-WHT-2431) • Water inlet: ½" water supply connection from left. • Flush volume: Factory setting 6.0~3.0 litres, Eco adjustable: 4.0~2.0 litres (Only for WC pans designed for low volume flushing).
Application	• For Front or Top actuation optional • For masonry walls installation • For installation in part-height prewall installations • Suitable for use with floor-standing or Wall Hung WCs • Small or large bathrooms, where space is at a premium, while ease of cleaning and sleek design is a priority. • All common construction systems, in domestic, commercial, industrial and institutional new build or refurbishment projects.
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	