


BATH + LIGHT

STRIP LIGHT 40W

INDOOR STIRP LIGHT Indoor Luminaire Product Code: LSTP03X008XC / LSTP03X008XN / LSTP03X008XW 40W - 3600Im - 6500K - CRI>80 Ra - Beam Angle - 120°





Technical Specifications

Operating Temperature Rated Input Voltage & Frequency Rated Input Wattage Rated Input Current Rated Input Voltage Rated Luminous Flux Rated Luminaire Efficacy Correlated Color Temperature (CCT) Color Rendering Index (CRI) Beam Angle LED Life Span Housing Lens / Reflector Mounting -10°C to 40°C 220-240 VAC, 50Hz 40W ± 10% 2.0 Amp (Nominal) 24VDC±0.5V 3600 lm / 3400 lm / 3200 lm (tolerance as per BIS) 90 lm/W / 85 lm/W / 80 lm/W (tolerance as per BIS) 6500 K / 4000 K / 3000 K (tolerance as per ANSI) >80 Ra 120° (within the permissible limits) >50000 Hrs (Ta=25°C @L70) Thick Double Layer Copper Flexible PCB NA Surface (With 3M Double Sided adhesive Tape)

Protections


Ingress Protection (IP Rating)

IP20

All technical data is subject to industry-standard tolerances.

Product Dimensions (W x H), Length

8 X 2.5mm, 5 Meter



Applications

Applications Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.