jaquar.com	
Document No.	
SNW/OPS/25/961NBIUFSM	TLE
	Image: sensor for flush Image: sensor for flush Image: sensor flush Image: sensor for flush <
	SIDE VIEW BACK VIEW
GENERAL INFORMATION	
Product Code	OPS-WHT-15961NBIUFSMTL
Brand	Jaquar
Colour	White
Туре	Tankless Wall Hung WC
Material	Ceramic-Vitreous China (VC)
PRODUCT SPECIFICATION	
Product Dimension	360x580x380 mm
Bowl Inner Dimension	255x340 mm
Product Net Weight	33 kg.
Product Gross Weight	39 kg.
Packaging Dimension	640x480x490 mm
Outlet	Horizontal
Waste Hole Dimension	External diameter of outlet hole Ø100 +5/-2 mm
PRODUCT FEATURES	
Product Features	 Touch free technology • Single flush water saving • Hygienic ceramic surface High efficiency toilet: Single flush in 3 cycles, Laser sensor flushing, Single Flush-5 LPF, IP Rating - IP68, No cistern or flush valve is needed, Required only water supply with minimum dynamic pressure of 1.5 to 5.0 bar UF Soft closing seat cover for superior durability, • Scratch resistant Laser light can be adjusted to right or left.
ACCESSORIES INCLUDED	
UF soft close seat cover	OPS-WHT-15107UF
Rubber Gasket	ZPS-BLK-GK02
Angle Valve	ZPS-WHT-TL008
ACCESSORIES RECOMMENDATION	
Rack bolt	ZPS-MST-RB07
CARE AND CLEANING GUIDELINES	
- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.	
The product is heavy and it is recommended that two persons hold it while it is being fixed.	
¬ Carefully inspect the new product for damage before installation.	
¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.	
¬ Risk of external leakage. Do not lift or rock the bowl after placement.	
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
eg Do not allow cleaners to sit or soak on the product.	
Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
"DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product.Last modified on 05 May 2025.	