





5 1 · 6 ·	Tour our 4570
Product Code	OHS-CHR-1679
Description	Maze Prime Square Shape Single Function Shower 450 X 450mm AISI 304 stainless steel with
	RGB LED light remote control & installation kit for false ceiling
	• Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller,
	connecting to AC 100-240V, 50-60Hz
Flow Rate	47.00 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GB-8.0 LPM,
	& GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Single Function
	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08,
	Iron Remainder (AISI 304)
Material Composition	in the manual () as so if
Specification in Percentage	ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell
	Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
REMOTE CONTROL	
	ON/OFF • ON
	Automatic mode changing - next Speed Down Panoramic Mode ON
	Push - button to speed down pancramic mode Speed Up
	Mono color - next •
	Mono color - previous •
	Automatic mode changing previous
	Jaquar
	Release
	Push Push HOW TO CHANGE BATTERY
	- HOW TO GRANDE DATE IT
LED POWER SUPPLY	CHROMO THERAPY (RGB) •
	LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz
	COLOR VARIATION • Mono Color (RGB) Chromo Theraphy
	Mono Color (RGB) Chromo Theraphy
	1000
	LED On / Off
	Switch Sensor by Remote Control
	Advanced Bulkis Live and devenies with a sharp and a second by a silver who a
Technology	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand
Registered design no.	or flannel. 276017
negistered design no.	
Finish	Salt Spray (350 hrs + Validated)
	Adhesion (Pass)
Available Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite
-	(GRF) & Stainless Steel Finish (SSF)
	s been made to ensure factual accuracy, the information presented subject to changes due to
requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to	

make the necessary amendments at any time without prior notice.