



Product code	SNR-CHR-51085K
Description	Exposed Part Kit of Urinal Sensor Consisting of Wall Flange with Sensor Eye & (4 X 1.5V AA) Batteries (Compatible with SNR-51085C)
Input rated voltage supply	DC-6V (4X1.5V AA Alkaline Battery)
Default Parameters	Detection Range : 600mm +/- 10% Pre-Flush Time : 3 - 4 seconds +/-10% Post-Flush Time : 6 - 8 Seconds +/-10%
Power consumption	Standby Mode : DC ≤ 0.2mW Flushing Mode: DC ≤ 4.0W
Hygenic Flushing	System will self-clean once every 24 hours if no one uses it.
LED Indication	LED blinks once at each sensing
Ingress Protection (Sensor Eye)	IP67
Flow regulator	Product should be ordered with suffix GHLT - 0.5 LPF, G - 1.5 LPF & G1 - 1.0 LPF @ 3.0 Bar pressure one can regulate the flow rate
Material Composition Specification in Percentage	Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Available Color Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF), & Stainless Steel (SSF)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in default parameters may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.