



TOP VIEW



SIDE VIEW



BACK VIEW

GENERAL INFORMATION	
Product Code	DIS-WHT-93951UF
Brand	Jaquar
Colour	White
Type	Wall Hung WC
Material	Ceramic-Vitreous China (VC)
PRODUCT SPECIFICATION	
Product Dimension	350x750x340 mm
Bowl Inner Dimension	265x300 mm
Product Net Weight	30 kg.
Product Gross Weight	34.7 kg.
Packaging Dimension	800x400x400 mm
Outlet	Horizontal
Inlet And Outlet Hole Dimension	Internal diameter of inlet hole dia. $\varnothing 58 \pm 3$ mm
	External diameter of outlet hole dia. $\varnothing 100 \pm 5$ mm
PRODUCT FEATURES	
Product Features	Designed for Specially Aabled People, Soft Close Seat Cover, Trapwash, Dual Flush-3/6 LPF,Anti germ glaze.
ACCESSORIES INCLUDED	
UF soft close seat cover	DIS-WHT-93103UF
Inlet & Outlet gasket	ZPS-WHT-GK01
ACCESSORIES RECOMMENDATION	
Rack bolt	ZPS-MST-RB07N
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
CARE AND CLEANING GUIDELINES	
→ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.	
→ The product is heavy and it is recommended that two persons hold it while it is being fixed.	
→ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.	
→ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.	
→ Risk of external leakage. Do not lift or rock the bowl after placement.	
→ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
→ Do not allow cleaners to sit or soak on the product.	
→ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
→ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
→ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
→ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
→ Recommended to use Genuine Accessories.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.	
# For Installation Refer Actual Product.Last modified on 23 August 2025.	