




Product Code	ALD-CHR-083FT
Description	Regular body of concealed stop cock suitable for 15mm pipe line with plastic protection cap (without Exposed Parts)
Flow Rate	61.00 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Cartridge Specification	Cartridge Specification = M24X1.5P (Approx. 3/4"), Multi/Full turn Cartridge. Life Cycle = 2Lac. Max.Hot Water 90°(Recommended 65°) Grease Quality = Klubersynth VR 69-252 N to be used. Washer Quality = Rubber NBR type to be used.
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Available Colour Finishing	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	