



<b>Product Code</b>	FLV-CHR-1075FP
<b>Description</b>	i-Flush 20mm Concealed Body with Floor Mounting Frame, Installation Kit and “P-Type” Drain Pipe Connection Set for Wall Hung WC (without Exposed Actuation Plate Kit)
<b>Flow Rate</b>	1.2 LPS @ 3 bar
<b>Recommended Water Pressure</b>	1.5 Bar - 4.0 Bar (Dynamics)
<b>Brass Specification in Percentage</b>	<p><b>Brass Ingots as per IS:1264-1997</b> Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Pipe as per IS:407-1996</b> Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p>
<b>Frame</b>	MS Frame (Power Coated)
<b>Drainage Pipe</b>	HDPE (High Density Poly Etylene)
<b>Finish</b>	Salt Spray(350 hrs + Validated) Adhesion( Pass)
<b>Available Colour Finishing</b>	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	