





OHS-CHR-1629
OHS-XXX-1629PD
Maze Overhead Shower 240X240mm Square Shape Single Flow (Body & Face Plate
Stainless Steel) with Rubit Cleaning System
37.91 LPM @ 3 bar
By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-
6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow
rate.
0.5 Bar - 3.0 Bar
Wall Mounting
Single Function
Brass Rod as per IS:319-1989
Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon
0.0-0.08, Iron Remainder (AISI 304)
ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26,
Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off
by hand or flannel.
276017
Salt Spray (350 hrs + Validated)
Adhesion (Pass)
ntique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), raphite (GRF) & Stainless Steel Finish (SSF)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.