





OHS-CHR-1755
Overhead Shower 180mm Round Shape Single Flow with Air Effect (ABS Body & Face
Plate Chrome Plated) with Rubit Cleaning System
13.63 LPM @ 3 bar
By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-
6.0 LPM, GB-8.0 LPM & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow
rate.
1.0 Bar - 3.0 Bar
Wall Mounting
Single Function
Brass Rod as per IS:319-1989
Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
ABS Specification
Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell
Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)
Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a
part of the shower. This leads to lighter voluminous drops which reduce water
consumption by 30% and also assuring a soft and refreshing shower
Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off
by hand or flannel.
Salt Spray (350 hrs + Validated)
1
Adhesion (Pass)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.