



TOP VIEW



SIDE VIEW



BACK VIEW


GENERAL INFORMATION

Product Code	ACS-WHM-87953NBIUF
Brand	Jaquar
In Colours	White Matt, Grey Matt, Beige Matt, Black Matt
Type	Wall Mounted WC - P TRAP
Material	Ceramic-Vitreous China (VC)

PRODUCT SPECIFICATION

Product Dimension	380x520x375 mm
Bowl Opening (Inner Dimension)	290x330 mm
Product Net Weight	23.0 Kg
Product Gross Weight	28.0 Kg
Packaging Dimension	455x385x530 mm
Outlet	Horizontal
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole $\varnothing 55 +3/-1$ mm
	External diameter of outlet hole dia. $\varnothing 100 \pm 5$ mm
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 220 mm

PRODUCT FEATURES

Stylish Rimless Design With Round Shape UF Soft Close Seat Cover Water Usage - 4.5/3 LPF With Wash Down Flushing Anti Bacterial Glaze on Ceramic Anti Bacterial Seat Cover Smooth Glaze Surface Material - Vitreous China (VC) Product With Complete Genuine Accessories Complete Tran Wash	(L) From wall tile surface to center of seat cover fixing hole (La) WC Fixing wall thickness (Lb) From wall tile surface to the inner bowl surface of WC 
---	---

ACCESSORIES PROVIDED

UF Soft Close Seat Cover	ACS-WHM-87101UF, ACS-BLM-87101UF, ACS-BEM-87101UF, ACS-GRM-87101UF,
Inlet outlet Gasket	ZPS-WHT-GK01
Fixing kit	ZPS-WHT-FB13

ACCESSORIES RECOMMENDATION

Rack bolt	ZPS-SNS-RB07N
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS

CARE AND CLEANING GUIDELINES

- ☑ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ☑ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ☑ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- ☑ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- ☑ Risk of external leakage. Do not lift or rock the bowl after placement.
- ☑ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ☑ Do not allow cleaners to sit or soak on the product.
- ☑ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ☑ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ☑ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ☑ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- ☑ Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.

For Installation Refer Actual Product. Last modified on August 2026.