




Technical Details

Product Code	VER-CHR-97053
Description	Angular Stop Cock with Wall Flange
Flow Rate	20.70 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
Material Specification in Percentage	Brass Ingots as per IS:1264-1997 / CuZn39Pb1Al-C or CC757S Cu (58.0-63.0), Sn (0.0-0.5), Pb (0.8-1.4), Ni (0.0-0.2), Al (0.4-0.8), Fe (0.0-0.3), Mn (0.0-0.5), Total Impurity (0.0-0.02), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) S.S Sheets as per AISI : 304 Ni (8.0-11.0), Ch (18.0-20.0), Mn (0.0-0.2), Ca (0.0-0.08), Fe (Remainder)
Cartridge Specification	Fittings : Components have WRAS Approved for food grade conformity with Brass Housing and Spindle Life Cycle EN 200: 200,000 cycles (Standard) - 5.0 LAC Cycles as per EN 200*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Available Colour Finishing	Chrome (CHR), Black Chrome (BCH) & Black Matt (BLM)

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.